

you can  
**Canon**

**iPF605 / iPF610**

Large Format  
Print Solutions

Perfect for CAD & GIS printing

iPF605 / iPF610

The imagePROGRAF iPF605 and iPF610 are 5 colour dye/pigment ink 24" large format printers, ideal for printing fine lines, re-creating vivid colours and producing high quality detailed images. With a 1,200 dpi resolution, solid image consistency and high quality text reproduction these printers are perfect for the CAD/GIS market.



Sharper, thinner lines and high black density for CAD plan production

Great colour output with brilliant text and less abrasion

Economy Printing Mode for lower running costs.

Superb graphics with vivid colours and solid image consistency

Incredible print speeds – A1 in 33 seconds



iPF605

*We Speak Image*

<b>24</b> inch	2,400 x 1,200dpi	<b>4</b> pl	<b>5</b> colours	A1 33 seconds	15,360 nozzles	HPGL/2 & HP RTL Compatible	Borderless Printing
-------------------	------------------------	-------------	---------------------	------------------	-------------------	----------------------------------	------------------------

- HPGL/2 and HP RTL compatibility and includes HDI Driver for CAD applications as standard.
- Large LCD with graphics ensures easy operation.
- High performance, high durability cutter incorporated for a professional finish.
- Compact and quiet - its the output not the noise that gets you noticed.

Class Ink Type	24-inch Pigment and Dye reactive ink, 5 colours (MBK x 2, BK, C, M, Y)
Maximum Print Resolution	2,400 x 1,200 dpi
Printing Speed (A1 Roll, Full Colour Image)	0:33 (Fast-CAD)
Plain paper	1:19 (Standard-CAD)
Coated Paper	2:44 (Standard-Full Colour Image)
Photo Glossy Paper	
Dimensions, Weight (Net)	
W x D x H (mm), (kg)	
iPF605	997 (W) x 670 (D) x 344 (H) mm; Weight approx. 45 kg
Main Unit with stand	997 (W) x 870 (D) x 993 (H) mm; Weight approx. 60 kg
iPF610	
Main Unit	997 (W) x 810 (D) x 344 (H) mm; Weight approx. 51 kg
Main Unit with stand	997 (W) x 991 (D) x 989 (H); Weight approx. 68 kg
Dimensions, Weight (Packaged)	
W x D x H (mm), (kg)	
iPF605	1,140 (W) x 914 (D) x 645 (H) mm; Weight approx. 69 kg
Main unit with palette	1,115 (W) x 864 (D) x 237 (H) mm; Weight approx. 22 kg
Printer Stand	
iPF610	1,138 (W) x 914 (D) x 675 (H); Weight approx. 74 kg
Main unit with palette	1,115 (W) x 864 (D) x 237 (H) mm; Weight approx. 22 kg
Printer Stand	
Power Supply	
Input power	AC 100 - 120 V (50/60 Hz) - AC 220 - 240V (50/60Hz)
Power consumption	100 W or less
Standby power consumption (At the low power mode)	6 W or less (when IEEE1394 is mounted, 11 W or less)
220 V - 240 V	5 W or less (when IEEE1394 is mounted, 10 W or less)
100 V - 120 V	1 W or less (In compliance with Executive Order of the President of the United States of America)
Power off (standby)	Temperature: 15 - 30°C, Humidity: 10 - 80% (Condensation free)
Operational Environment	
Acoustic Noise	Operation: 49dB (A) or less (iPF605)/52dB (A) or less (iPF610), Standby 35dB (A) or less
Acoustic pressure	Operation: 6.3 Bels or less (iPF605)/6.6 Bels or less (iPF610)
Acoustic power	0.02 mm (Theoretical value)
Minimal Line Width	±0.1 % or less (User adjustments necessary. Printing environment media must match that used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only.)
Line Accuracy	Large LCD: 160 x 128 dots, Key x 12, LED x 5
Operation Panel Display	US-English, Japanese
Language on operation panel	bUS-English, French, German, Italian, Spanish, Chinese, Korean, Japanese (Kanji), Russian
Displayable Language on LCD	GARO, HP-GL/2, HP RTL
Printer Language	
Interface	
USB2.0 Hi-Speed	Built-in
Type	IEEE 802.3 10base-T
Mode	IEEE 802.3u 100base-TX / Auto-Negotiation
Connector type	IEEE 802.3 x Full Duplex
Ethernet	IPX/SPX (Netware 4.2(J), 5.0(J), 6.0(J) )
Type	SNMP (Canon-MIB), HTTP, TCP/IP, AppleTalk
Standard	
Protocol	
IEEE1394 (Option)	Slot card type
Type	IEEE1394 - 1995, P1394a, Half duplex, Data/Strb differential serial
Standard	100 / 200 / 400 Mbit/sec.
Data-transfer time	In compliance with IEEE1394 - 1995, 6 pins, No power supply
Connector type	Windows 2000, XP, Server 2003, Vista / Macintosh OS 9, OS X
Operating Systems supported	CE Mark, CB Certification, TUV (GS), Gost-R, UL, FCC class B
Regulations	
<b>PRINT HEAD</b>	
Model	PF-03
Type	Bubble-jet on demand
Head configuration	6 colours integrated type (6 chips per print head)
Nozzle pitch	1,200 dpi x 2
Nozzle per chip	MBK: 5,120 nozzles, Other Colours: 2,560 nozzles each
Droplet size	4 pl per colour

<b>INK TANK</b>	
Model	PFI-102 (130 ml) MBK, BK, C, M, Y
<b>Media Handling</b>	
Roll paper	Top-loading, front output (front feeding, front output for thick media)
Cut sheet	Front-loading, Front Output
Cut Sheet (Cassette - iPF610 only)	Front loading, front output
Media type	
Roll paper	Standard Paper 80 gsm, Standard Paper 90 gsm, Matt Coated Paper 90 gsm, Glossy Photo Quality Paper 190 gsm / 240 gsm / 300 gsm, Satin Photo Quality Paper 190 gsm / 240 gsm / 300 gsm, Photo Realistic Paper 210 gsm, Pearl Photo Paper 260 gsm, Matt Coated Paper 120 gsm / 140 gsm / 180 gsm, Opaque White Paper 120 gsm, High Resolution Self-adhesive Graphic Paper 140 gsm, High Resolution Barrier Paper 180 gsm, Glossy Proofing Paper 195 gsm, Semi-Glossy Proofing Paper 195 gsm / 255 gsm.
<b>Media Size</b>	
Roll paper (width)	ISO: A3, A2, A1, JIS: B4, B2, ARCH: D 24" Others: 8", 10", 14", 16", 17", 300 mm, A3+ (329 mm)
Cut Sheet	ISO: A4, A3, A3+, A2, A1, B4, B3, B2, DIN: C4, C3, C2, JIS: B4, B3, B2, ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22", 22 x 34", ARCH: 9 x 12", 12 x 18", 18 x 24", 24 x 36", Photo: 20 x 24", 18 x 22", 14 x 17", 12 x 16", 10 x 12", 10 x 15", 16 x 20" (US Photo size), Poster: 20 x 30", 300 x 900 mm, Others: 13 x 22", 17 x 24"
Cut Sheet (Cassette) (Cassette - iPF610 only)	ISO: A4, A3, A3+, A2, JIS: B4, B3, ANSI: 8.5 x 11", 8.5 x 14", 11 x 17", 13 x 19", 17 x 22"; ARCH: 12 x 18"; Photo: 14 x 17", 12 x 16", 10 x 12", 10 x 15", 8 x 10", 16 x 20" (US Photo size); Others: 13 x 22"
<b>Media Thickness</b>	Roll paper & Cut sheet: 0.07 - 0.8 mm
Maximum Outside Diameter of Roll Paper	150.0 mm
Media Core Size	Internal diameter of roll core: 2" / 3" (Option)
Media Width	Roll paper: 203 - 610 mm Cut sheet: 203 - 610 mm
<b>Minimal Printable Paper Length</b>	203 mm
<b>Maximum Printable Paper Length</b>	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
<b>Margins (Top, Bottom, Sides) Recommended area</b>	Roll paper: Top: 20 mm, Bottom: 5 mm, Side: 7 mm Cut Sheet (Top loading/Cassette): Top: 20 mm, Bottom: 27 mm, Side: 5 mm Cut Sheet (Front Loading) Top: 20 mm, Bottom: 23 mm, Side: 5 mm Roll paper (borderless print): Top: 0 mm, Bottom: 0 mm, Side: 0 mm Cut Sheet (Front loading) Top: 3 mm, Bottom: 23 mm, Side: 3 mm Cut Sheet (Top loading/Cassette): Top: 3 mm, Bottom: 3 mm, Side: 3 mm
<b>Printable area</b>	10" (254 mm), B4 (257 mm), A3+ (329 mm), 14" (356 mm), 16" (407 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 mm), A1 (594 mm), 24" (610 mm)
<b>OPTION</b>	
Printer Stand	ST-24
Roll Holder Set	RH2 - 24 (2-inch core spindle with 3-inch media tube attachment and borderless printing space)
IEEE1394 Expansion Board	EB-05
<b>CONSUMABLES</b>	
Ink Tank	PFI-102 (130 ml) ; MBK, BK, C, M, Y
Print Head	PF-03
Maintenance Cartridge	MC-16

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.



**Canon Inc.**  
www.canon.com

**Canon Europa N.V.**  
www.canon-europe.com

English-UK Edition 0127W498 -  
5026173428705  
© Canon Europa N.V., 2008 (0908)

**Canon (UK) Ltd**  
Woodhatch, Reigate  
Surrey RH2 8BF  
Telephone No: 01737 220000  
Facsimile No: 01737 220022  
www.canon.co.uk

**Canon Ireland**  
Arena Road, Sandyford Industrial Estate  
Dublin 18, Ireland  
Telephone No: 01-2052400  
Facsimile No: 01-2958141  
www.canon.ie

